

T



66HL4M-(V) 610-635 Watt

Mechanical Characteristics

5W*FkbW	@ žrkbW? a` a žJkfeS^f W
@ažaXUW'e	#%\$((° \$fi
6[W e[a` e	\$%\$° ##%&° % _ _
I WYZf	\$*ž\$]Y
8d` f 9'See	%ž\$ _ ! 3` f[ždW VUW[a` 5aSf[YI : [YZ FdS` e_ [ee[a` t >ai :d` t FVW_ bWVW 9'See
8dS_ W	3` aV[! VW 3'g_ [[g_ 3^ak
<g` Uf[a` 4aj	;B(* DSfVW
BdāfWUf[a` 5'See	5'See;;
:75 8[dMfkbW	5'See 5
5a` ` WUfadFkbW	<=" %? !? 5&! AfZVde
Agfbgf 5ST Wē	&Z' _ _ s /Efj &" _ _ t/žj \$" _ _ ad5gefa_ [! VW >W YfZ

Packaging Configuration

BS^W 6[W e[a` e	\$%+(° ##^° #S' # _ _
BSU[Y VVWS[^ /Fi a bS^W e/A` WefSU] fi	%# bUe! bS^W e! (\$ bUe! efSU] t ("\$ bUe! &" r: C 5a` fS[W!

Specifications (STC)


? S] [g_ Bai Wd B_ Sj M bO	(#" (#' (\$' (\$' (%' (%'
? S] [g_ Bai Wd Ha fSYW H_ b MIO	&" ž (&" ž) % &" ž+ &" ž') &#ž\$% &#ž'+
? S] [g_ Bai Wd 5gdW f ;_ b NBO	#' ž' & #' ž## #' ž#(#' ž\$ \$ #' ž\$* #' ž'&
A bW žU[djg[f Ha fSYW HaU MIO	&* ž' % &* ž) + &* ž+' &+ž## &+ž\$) &+ž&%
E Z ad žU[djg[f 5gdW f :eU NBO	#(ž' # #(ž' * #(ž# #' (ž\$ \$ #(ž\$+ #(ž')
? aVg W7 U[W Uk EF5 M O	\$ž\$ * \$žž) \$žž+' \$žž#& \$žž/\$ \$žž/ #
Bai Wd Fa WdS` UW	" p t %
FVW_ bVdSfgdM5aW U[W feaXB_ Sj	ž ž\$, !, 5
FVW_ bVdSfgdM5aW U[W feaXHaU	ž ž\$, !, 5
FVW_ bVdSfgdM5aW U[W feaXeU	" ž & , !, 5

EF5 :dSV[S` UM#""! I !_ ž 5W*FVW_ bVdSfgdM5` ,5I 3? /#Z

Application Conditions

A bVdSf[Y FVW_ bVdSfgdW	ž&" , 5 p t) " , 5
? S] [g_ EkefW_ Ha fSYW	#""!#"" H65/;75fi
? S] [g_ EVdWē 8geWDSf[Y	% 3


Engineering Drawings



f!@afW8adebWU[UVL W eja` eS` V fa VdS` UMdS` YWd b VdSeW
d/Wd fa fZVUad t/Mba` V[Y VVWS[VW _ aVg WdSi [Yez

Electrical Performance

Power-Voltage Curves (66HL4M- V 615W)



Current-Voltage Curves (66HL4M-(V) 615W)

